



## ZSAR13020



- Aluminium body.
- Only to be used with electronic Led driver.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- 1-10V, DALI and switch dimming options available upon request.
- Clear safety glass.
- Basic colours: white, black, silver and special color options available upon request.
- Honeycomb filter accesorie available.
- Narrow, medium and wide beam angle options available with rotationally symmetric light distribution.
- Steel suspension chain up to 5mt lenght option.

- Alüminyum gövde.
- Yalnızca elektronik Led trafo kullanımı için uygundur.
- 220-240V / 50-60Hz enerji girişli.
- Akıllı soğutma tasarımı.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- Tamperli cam.
- Standart renkler: beyaz, siyah, gri ve isteğe bağlı özel renk seçeneği mevcuttur.
- Bal peteği filtre aksesuar seçeneği mevcuttur.
- Simetrik ışık çıkışı sağlayan dar, orta ve geniş açılı reflektör seçenekleri mevcuttur.
- 5mt uzunluk seçeneğine kadar mevcut çelik sarkıtma teli.

COB LED	Philips (39)		
Led Power / Led Gücü	2x32W		
System Power / Sistem Gücü	2x35W	2x35W	2x35W
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	6800	7200
	3000K	7800	8200
	4000K	8300	8500
	5000K	X	X
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>90	2700K	6100	6500
	3000K	6900	7300
	4000K	X	X
	5000K	X	X
Meat / Et COB	2000K	3900	3900
Food / Gıda COB	2500K	4500	4500
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	✓	✓	✓
1-10V Dimming Option / 1-10V Dim Seçeneği	✓	✓	✓
Dali Dimming Option / Dali Dim Seçeneği	✓	✓	✓

Honeycomb Filter	Suspension Cord
Petekli Filtre	Ray Sarkıtma Teli

