




ZSAR13095



- Aluminium body.
- Only to be used with electronic Led driver.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- 1-10V, DALI and switch dimming options available upon request.
- Clear safety glass.
- Basic colours: white, black, silver and special color options available upon request.
- Honeycomb filter accesorie available.
- Narrow, medium and wide beam angle options available with rotationally symmetric light distribution.
- Emergency kit system can be integrated.
- Steel suspension chain up to 5mt lenght option.

- Alüminyum gövde.
- Yalnızca elektronik Led trafo kullanımı için uygundur.
- 220-240V / 50-60Hz enerji girişli.
- Akıllı soğutma tasarımı.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- Tamperli cam.
- Standart renkler: beyaz, siyah, gri ve isteğe bağlı özel renk seçeneği mevcuttur.
- Bal peteği filtre aksesuar seçeneği mevcuttur.
- Simetrik ışık çıkışı sağlayan dar, orta ve geniş açı reflektör seçenekleri mevcuttur.
- Acil aydınlatma kit sistemi uygulanabilir.
- 5mt uzunluk seçeneğine kadar mevcut çelik sarkıt teli.

COB LED	Philips (39)	Tridonic (44)	Cree (06)
Led Power / Led Gücü	3x32W	3x32W	3x32W
System Power / Sistem Gücü	3x35W	3x35W	3x35W
Lumen Output from Fixture / Armatür Çıkış Lümeni	2700K	10200	10800
	3000K	11700	12300
	4000K	12450	12750
	5000K	X	X
Lumen Output from Fixture / Armatür Çıkış Lümeni	2700K	9150	9750
	3000K	10350	10950
	4000K	X	X
	5000K	X	X
Meat / Et COB	2000K	5850	5850
Food / Gıda COB	2500K	6750	6750
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	✓	✓	✓
1-10V Dimming Option / 1-10V Dim Seçeneği	✓	✓	✓
Dali Dimming Option / Dali Dim Seçeneği	✓	✓	✓

Honeycomb Filter	Suspension Cord
Petekli Filtre	Ray Sarkıtma Teli

