





## ZSAR13100



- Aluminium body.
- Only to be used with electronic Led driver.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- 1-10V, DALI and switch dimming options available upon request.
- Clear safety glass.
- Basic colours: white, black, silver and special color options available upon request.
- Honeycomb filter accesorie available.
- Narrow, medium and wide beam angle options available with rotationally symmetric light distribution.
- Emergency kit system can be integrated.
- Steel suspension chain up to 5mt lenght option.

- Alüminyum gövde.
- Yalnızca elektronik Led trafo kullanımı için uygundur.
- 220-240V / 50-60Hz enerji giriřli.
- Akıllı soğutma tasarımı.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- Tamperli cam.
- Standart renkler: beyaz, siyah, gri ve isteğe baęlı özel renk seçeneęi mevcuttur.
- Bal peteęi filtre aksesuar seçeneęi mevcuttur.
- Simetrik ışık çıkışı saęlayan dar, orta ve geniş açılı reflektör seçenekleri mevcuttur.
- Acil aydınlatma kit sistemi uygulanabilir.
- 5mt uzunluk seçeneęine kadar mevcut çelik sarkıt teli.

COB LED	Philips (39)	Tridonic (44)	Cree (06)
Led Power / Led Gücü	4x32W	4x32W	4x32W
System Power / Sistem Gücü	4x35W	4x35W	4x35W
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	13600	14400
	3000K	15600	16400
	4000K	16600	17000
	5000K	X	X
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>90	2700K	12200	13000
	3000K	13800	14600
	4000K	X	X
	5000K	X	X
Meat / Et COB	2000K	7800	7800
Food / Gıda COB	2500K	9000	9000
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	✓	✓	✓
1-10V Dimming Option / 1-10V Dim Seçeneęi	✓	✓	✓
Dali Dimming Option / Dali Dim Seçeneęi	✓	✓	✓

Honeycomb Filter	Suspension Cord
Petekli Filtre	Ray Sarkıtma Teli

