


ZAP6025



- Corrosion resistant die cast aluminium alloy.
- Thermal shock resistant safety glass.
- Weatherproof and durable silicone rubber gasket.
- Ultraviolet stabilized polyester powder coat finish in black, dark gray and light gray finish.
- Convenient to be used with COB LED option.
- Designed for single-side light output.
- Luminaire can be installed in any burning position.
- All external screws are stainless steel.

- Korozyona dayanıklı alüminyum gövde.
- Paslanmaz çelik vida.
- Tamperli cam.
- Su geçirmezliği sağlayan plastik conta.
- Ultraviyole ışımaya dayanıklı beyaz, gri, saten gri ve siyah elektrostatik toz boyalı.
- Tek taraftan ışık çıkışı olacak şekilde tasarlandı.
- Armatür aşağı veya yukarı bakacak şekilde istenildiği gibi monte edilebilir.
- Tüm dış vidalar paslanmaz çelik.



LED	COB LED
Led Power / Led Gücü	32W
System Power / Sistem Gücü	35W
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K
	3000K
	4000K
	5000K
	3400
	3900
	4150
	4400

Beam Angle: 20° (Micro Silver)

Distance (m)	Beam Diameter (m)	Mounting (m)	Height (m)
0.5	0.17	E1/F1 E(C)/1	7248 34537
1.0	0.35	E1/F1 E(C)/1	14112 654
1.5	0.52	E1/F1 E(C)/1	8055 3837
2.0	0.69	E1/F1 E(C)/1	4053 2133
2.5	0.87	E1/F1 E(C)/1	2882 1381
3.0	1.04	E1/F1 E(C)/1	2001 939

Beam Angle: 30° (Micro Silver)

Distance (m)	Beam Diameter (m)	Mounting (m)	Height (m)
0.5	0.30	E1/F1 E(C)/1	21688 23822
1.0	0.48	E1/F1 E(C)/1	12887 5655
1.5	0.72	E1/F1 E(C)/1	5712 3647
2.0	0.96	E1/F1 E(C)/1	3228 1489
2.5	1.20	E1/F1 E(C)/1	2064 953
3.0	1.44	E1/F1 E(C)/1	1433 662

Beam Angle: 50° (Micro Silver)

Distance (m)	Beam Diameter (m)	Mounting (m)	Height (m)
0.5	0.48	E1/F1 E(C)/1	18034 8620
1.0	0.96	E1/F1 E(C)/1	4509 2158
1.5	1.44	E1/F1 E(C)/1	2004 758
2.0	1.92	E1/F1 E(C)/1	1127 426
2.5	2.40	E1/F1 E(C)/1	721 273
3.0	2.88	E1/F1 E(C)/1	504 189

