



ZAP6040



- Corrosion resistant die cast aluminium alloy.
- Thermal shock resistant safety glass.
- Weatherproof and durable silicone rubber gasket.
- Ultraviolet stabilized polyester powder coat finish in black, dark gray and light gray finish.
- Convenient to be used with COB led option.
- Designed for single-side light output.
- Luminaire can be installed in any burning position.
- All external screws are stainless steel.

- Korozyona dayanıklı alüminyum gövde.
- Paslanmaz çelik vida.
- Tamperli cam.
- Su geçirmezliği sağlayan plastik conta.
- Ultraviyole ışımaya dayanıklı beyaz, gri, saten gri ve siyah elektrostatik toz boyalı.
- Tek taraftan ışık çıkışı olacak şekilde tasarlandı.
- Armatür aşağı veya yukarı bakacak şekilde istenildiği gibi monte edilebilir.
- Tüm dış vidalar paslanmaz çelik.

LED		COB LED
Led Power / Led Gücü		2x23W
System Power / Sistem Gücü		2x25W
Lumen Output from Fixture / Armatür Çıkış Lümeni	2700K	2x2150
	3000K	2x2250
	4000K	2x2350
	5000K	2x2400

Beam Angle: 20° (Miro Silver)

Beam Angle (°)	Beam Diameter (m)	Height (m)	Beam Area (m²)
0.5	0.39	0.5	0.076
1.0	0.77	1.0	0.304
1.5	1.16	1.5	0.676
2.0	1.54	2.0	1.196
2.5	1.93	2.5	1.844
3.0	2.32	3.0	2.616

Beam Angle: 30° (Miro Silver)

Beam Angle (°)	Beam Diameter (m)	Height (m)	Beam Area (m²)
0.5	0.59	0.5	0.174
1.0	1.17	1.0	0.696
1.5	1.76	1.5	1.548
2.0	2.34	2.0	2.736
2.5	2.93	2.5	4.164
3.0	3.52	3.0	5.832

Beam Angle: 40° (Miro Silver)

Beam Angle (°)	Beam Diameter (m)	Height (m)	Beam Area (m²)
0.5	0.78	0.5	0.304
1.0	1.56	1.0	1.216
1.5	2.34	1.5	2.736
2.0	3.12	2.0	4.896
2.5	3.90	2.5	7.656
3.0	4.68	3.0	11.016

