



ZAPWA074



- Corrosion resistant die cast aluminium alloy.
- Thermal shock resistant safety glass.
- Weatherproof and durable silicone rubber gasket.
- Ultraviolet stabilized polyester powder coat finish in black, dark gray and light gray finish.
- Convenient to be used with COB led option.
- Designed for single-side light output.
- Luminaire can be installed in any burning position.
- All external screws are stainless steel.

- Korozyona dayanıklı alüminyum gövde.
- Paslanmaz çelik vida.
- Tamperli cam.
- Su geçirmezliği sağlayan plastik conta.
- Ultraviyole ışımaya dayanıklı beyaz, gri, saten gri ve siyah elektrostatik toz boyalı.
- Tek taraftan ışık çıkışı olacak şekilde tasarlandı.
- Armatür aşağı veya yukarı bakacak şekilde istenildiği gibi monte edilebilir.
- Tüm dış vidalar paslanmaz çelik.



LED	COB LED
Led Power / Led Gücü	23W
System Power / Sistem Gücü	25W
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K
	3000K
	4000K
	5000K
	2150
	2250
	2350
	2400

Beam Angle: 20° (Miro Silver)

Distance (m)	Beam Diameter (m)	Height (m)
0.5	0.10	0.50
1.0	0.20	1.00
1.5	0.30	1.50
2.0	0.40	2.00
2.5	0.50	2.50
3.0	0.60	3.00

Beam Angle: 30° (Miro Silver)

Distance (m)	Beam Diameter (m)	Height (m)
0.5	0.15	0.50
1.0	0.30	1.00
1.5	0.45	1.50
2.0	0.60	2.00
2.5	0.75	2.50
3.0	0.90	3.00

Beam Angle: 40° (Miro Silver)

Distance (m)	Beam Diameter (m)	Height (m)
0.5	0.20	0.50
1.0	0.40	1.00
1.5	0.60	1.50
2.0	0.80	2.00
2.5	1.00	2.50
3.0	1.20	3.00

