



ZAPWA076



- Corrosion resistant die cast aluminium alloy.
- Thermal shock resistant safety glass.
- Weatherproof and durable silicone rubber gasket.
- Ultraviolet stabilized polyester powder coat finish in black, dark gray and light gray finish.
- Convenient to be used with COB led option.
- Designed for single-side light output.
- Luminaire can be installed in any burning position.
- All external screws are stainless steel.

- Korozyona dayanıklı alüminyum gövde.
- Paslanmaz çelik vida.
- Tamperli cam.
- Su geçirmezliği sağlayan plastik conta.
- Ultraviyole ışımaya dayanıklı beyaz, gri, saten gri ve siyah elektrostatik toz boyalı.
- Tek taraftan ışık çıkışı olacak şekilde tasarlandı.
- Armatür aşağı veya yukarı bakacak şekilde istenildiği gibi monte edilebilir.
- Tüm dış vidalar paslanmaz çelik.

LED	COB LED	
Led Power / Led Gücü	2x23W	
System Power / Sistem Gücü	2x25W	
Lumen Output from Fixture / Armatür Çıkış Lümeni	2700K	2x2150
	3000K	2x2250
	4000K	2x2350
	5000K	2x2400
CRİ>80		

Beam Angle: 20° (Miro Silver)

Distance (m)	Beam Diameter (m)	Area (m²)
0.5	0.39	0.15
1.0	0.77	0.60
1.5	1.16	1.34
2.0	1.54	2.38
2.5	1.93	3.71
3.0	2.31	5.34

Beam Angle: 30° (Miro Silver)

Distance (m)	Beam Diameter (m)	Area (m²)
0.5	0.59	0.35
1.0	1.17	1.37
1.5	1.76	3.10
2.0	2.34	5.47
2.5	2.93	8.58
3.0	3.51	12.33

Beam Angle: 40° (Miro Silver)

Distance (m)	Beam Diameter (m)	Area (m²)
0.5	0.77	0.60
1.0	1.54	2.38
1.5	2.31	5.34
2.0	3.08	9.48
2.5	3.85	14.81
3.0	4.62	21.33

