

## ZSAR17070



GRAY

WHITE

BLACK



- Aluminium profile body.
- Only to be used with electronic Led driver.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- Basic colours: white, black, silver and special color options available upon request.
- Narrow and wide beam angle options available with rotationally symmetric light distribution.
- Steel suspension chain up to 5mt length option.

- Alüminyum profil gövde.
- Yalnızca elektronik Led trafo kullanımı için uygundur.
- 220-240V / 50-60Hz enerji girişi.
- Akıllı soğutma tasarımı.
- Standart renkler: beyaz, siyah, gri ve isteğe bağlı özel renk seçeneği mevcuttur.
- Simetrik ışık çıkışı sağlayan dar ve geniş açı reflektör seçenekleri mevcuttur.
- 5mt uzunluk seçeneğine kadar mevcut çelik sarkıtma teli.

COB LED	Bridgelux (01)	
Led Power / Led Gücü	13W	
System Power / Sistem Gücü	14W	
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	830
	3000K	865
	4000K	900
	5000K	970
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	X	
1-10V Dimming Option / 1-10V Dim Seçeneği	X	
Dali Dimming Option / Dali Dim Seçeneği	X	

### Suspension Cord

### Ray Sarkıtma Teli

