

ZWLRGB16020



Light Grey

Black

Textured Metallic

Dark Grey



- Corrosion resistant aluminium extruded body.
- Only to be used with electronicLed driver.
- Mains voltage: 220-240V / 50-60Hz.
- Cree XPG2 Led.
- Clever thermal design.
- Narrow, medium and wide beam angles available.
- RGB Color output.
- Suitable for illumination up to 10 meter height.
- It can be assembled both wall and ceiling with adjustable mounting legs.
- Suitable to control with DMX system.

- Korozyona dayanıklı alüminyum profil gövde.
- Yalnızca elektronik Led trafo kullanımı için uygundur.
- 220-240V / 50-60Hz enerji girişi.
- Cree XPG2 led uyumlu.
- Akıllı soğutma tasarımı.
- Dar, orta ve geniş açılı seçenekleri mevcuttur.
- RGB renk çıkışı.
- 10 metre yüksekliğe kadar aydınlatma sağlanır.
- Hareketli montaj ayakları ile tavana ve duvara monte edilebilir.
- DMX sistemine göre kontrol edilebilir.

Order Code / Sipariş Kodu	Led Type / Tipi	System Power / Sistem Gücü	Kelvin / Color	Lenght / Uzunluk (A)
O07.WL.16020.RGB.07	Cree XPG2	9.25W	RGB (R3,G3,B3)	330mm
O07.WL.16020.RGB.07	Cree XPG2	18.35W	RGB (R6,G6,B6)	604mm
O07.WL.16020.RGB.07	Cree XPG2	27.50W	RGB (R9,G9,B9)	930mm
O07.WL.16020.RGB.07	Cree XPG2	36.75W	RGB (R12,G12,B12)	1150mm

