



- Die-cast aluminium body.
- Only to be used with electronic Led driver.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- With 3-phase universal track adaptor.
- 1-10V, DALI and switch dimming options available upon request.
- Dimming option with integrated potentiometer.
- Clear safety glass.
- Basic colours: white, black, silver and special color options.
- Oval wide beam angle reflector.

- Alüminyum enjeksiyon gövde.
- Yalnızca elektronik Led trafo kullanımı için uygundur.
- 220-240V / 50-60Hz enerji girişi.
- Akıllı soğutma tasarımı.
- 3-Fazlı üniversal ray adaptörü.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- Opsiyonel olarak potansiyometre ile dim seçeneği mevcuttur.
- Tamperli cam.
- Standart renkler: beyaz, siyah, gri ve isteğe bağlı özel renk seçeneği mevcuttur.
- Oval geniş ışık açılı özel reflektör yapılı.

#### Purelite Bridgespot / I01.MLT.40239

COB LED	Bridgelux (01)	
Led Power / Led Gücü	42W	
System Power / Sistem Gücü	45W	
Lumen Output from Fixture / Armatür Çıkış Lümeni	2700K	4150
	3000K	4350
	4000K	4550
	5000K	4550
Lumen Output from Fixture / Armatür Çıkış Lümeni	2700K	3350
	3000K	3550
	4000K	3850
	5000K	4050
Meat / Et COB	2000K	2400
Food / Gıda COB	2500K	3850
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	✓	
1-10V Dimming Option / 1-10V Dim Seçeneği	✓	
Dali Dimming Option / Dali Dim Seçeneği	✓	